



by Honeywell

GWMPs Series

Description

The GWMPs Series manual pull stations feature high-quality, die cast metal construction. They are available in either single or dual action configurations with SPST switch, and terminal strip connections. The normally open contact, which closes when the pull station is activated, is rated for 1 amp, at 125 VAC or 30 VDC. The contacts are gold-plated to avoid risk of corrosion. All models in the series have been tested by UL for compliance to the latest requirements of the Americans with Disabilities Act (ADA).

Operation

Single Action Pull Station

To operate the single action pull station, do the following:

1. On the front of the pull station, pull the handle downward until the handle locks into place.
Be sure it is easily visible from up to 50 ft.
2. To reset the pull handle, insert the key to open the pull station.
3. Place the handle in the normal upright position and relock the pull station.

Note: A scored acrylic break rod is also supplied with each unit for applications where it is necessary.

Dual Action Pull Station

To operate the dual action pull station, do the following:

1. On the front of the pull station, push the PUSH bar so that it rotates inward and allows you to grasp the pull handle in a one-handed motion.
2. To reset the pull handle, insert the key to open the pull station.
3. Place the handle in the normal upright position and relock the pull station.

Note: The dual action models are also supplied with break rods.

Specifications

Switch Rating: 1 amp at 125 VAC, or 30 VDC

Pull Station

Dimensions: 4 3/4" H x 3 1/4" W x 1 1/8" D
(12.6 H x 8.2 W x 2.9 D cm)

Surface Mount

Backbox Dimensions: 4 3/4" H x 3 1/4" W x 2 1/4" D
(cast and sheet metal).
(12.6 H x 8.2 W x 5.7 D cm)

Color: Red with raised white letters.
White PULL bar with raised red letters.

Accessories: All models are supplied with one scored acrylic break-rod and a PK625 key.

Metal Manual Fire Alarm Stations



Figure 1 GWMPs-1T
(Single Action)



Figure 2 GWMPs-2
(Dual Action)

Features

- Complies with UL Standard S281.
- ADA compliant.
- Offers single or dual action configurations.
- Provides terminal strip connections.
- Allows you to reset using the same keys as a Gamewell-FCI enclosures.
- Includes surface mount backboxes available.
- Designed with high-gloss, red enamel finish on die-cast metal.
- Constructed of corrosion-resistant gold-plated contacts.

Ordering Information

Part Number Description

GWMPs-1T	Pull Station, Single Action, Terminals
GWMPs-2	Pull Station, Double Action, Terminals
PS-BB	Pull Station Backbox
PS-GR-12	Box of 12 acrylic break-rods



GAMEWELL-FCI

12 Clintonville Road, Northford, CT 06472-1610 USA • Tel: (203) 484-7161 • Fax: (203) 484-7118

Specifications are for information only, are not intended for installation purposes, and are subject to change without notice. No responsibility is assumed by Gamewell-FCI for their use.

©2016 by Honeywell International Inc. All rights reserved

www.gamewell-fci.com

9021-60914 Rev. B page 1 of 1